



Successor of R-Flat 12/3!

This 12,1" Super VGA monitor was developed for small space mounting. The 19" front panel with through holes and the integrated power supply guarantee easy installation in 19" cabinet.

Technical Data

Article	R-FLAT 12/8
Size	30.70 cm (12,1")
Pixel ratio	0.3075 x 0.3075 mm
Resolution	800 x 600
Picture Area	246 x 184.5 mm
Brightness	450 cd/m ² min.
Contrast	700:1
Viewing angle	80°/ 80° (R/L) / 65°/ 75° (U/D)
Back lighting	LED, MTBF 50.000 Std.
Colors	16,2 Mio. / 262 k
Response time	35 ms typ.
Line frequency	30 - 60 kHz
Frame frequency	56 - 75 Hz
Alignment	sep. TTL pos./neg.
Video standards	VGA, SVGA, XGA
Signal input	15pin D-Sub analog, DVI-D digital
Power supply	80-264 VAC / 47-63 Hz
Power consumption	12 W typ. / 13 W max.
Weight aprox.	4 kg
Standards, conformity	CE; RoHS
Dimensions (WxHxD)	84 TE / 6 HE
Protection	IP65 frontseitig (mit entspiegelter Glasscheibe)
Operation temperature	0° ~ +50° C
Storage temperature	-20° ~ +60° C
Mechanic	Frontplatte Alu natur eloxiert
Options	

© All rights reserved. All mentioned product and company names as well as logos are trademarks of the corresponding companies. SR SYSTEM-ELEKTRONIK GmbH reserves the right to change the included specifications without prior notice. The customer is responsible to keep up to date to the given informations. SR is in no way responsible for damage caused by this device and can't be held responsible for mistakes within this document.

Intel®, Intel® Core(TM), Intel® Atom(TM), are trademarks of the Intel Corporation in the U.S. and other countries. Microsoft® and Windows® are trademarks of the Microsoft Corporation in the U.S. and other countries. Linux® ist he registered trademark of Linus Tovalds in the U.S. and other countries.